

# リード線加工(バルク)品


## ■形状寸法

形状 記号・図	型名	寸法 (mm)									
		L	D	d	P	h	h <sub>1</sub>	K	ℓ	ℓ <sub>1</sub>	do
	RD-S2FL**** (050)	3.3	1.7	0.45	5.0±1.0	7min	-	-	-	-	-
	RD-S2FL**** (075)				7.5±1.0						
	RD-25FL**** (100)	6.3	2.3	0.6	10.0±1.0	7min	-	-	-	-	-
	RD-25FL**** (125)				12.5±1.0						
	RD-S1FL**** (100)	6.3	2.3	0.6	10.0±1.0	7min	-	-	-	-	-
	RD-S1FL**** (125)				12.5±1.0						
	RD-50FL**** (125)	8.5	2.8	0.6	12.5±1.0	7min	-	-	-	-	-
	RD-50FL**** (150)				15.0±1.0						
	RO-S2FL***** (050)	3.3	1.7	0.45	5.0±1.0	7min	-	-	-	-	-
	RO-S2FL***** (075)				7.5±1.0						
	RO-25FL***** (100)	6.3	2.3	0.6	10.0±1.0	7min	-	-	-	-	-
	RO-25FL***** (125)				12.5±1.0						
	RO-S1FL***** (100)	6.3	2.3	0.6	10.0±1.0	7min	-	-	-	-	-
	RO-S1FL***** (125)				12.5±1.0						
	RO-50FL***** (125)	8.5	2.8	0.7	12.5±1.0	7min	-	-	-	-	-
	RO-50FL***** (150)				15.0±1.0						
	RO-1FL***** (150)	11.0	3.7	0.7	15.0±1.0	7min	-	-	-	-	-
	RG (X) -12SFL**** (100)	6.3	2.5	0.6	10.0±1.0	10±2	-	-	-	-	-
	RG (X) -12SFL**** (125)				12.5±1.0						
	RG (X) -1SFL**** (125)	9.0	2.8	0.7	12.5±1.0	13±3	-	-	-	-	-
	RG (X) -1SFL**** (150)				15.0±1.0						
	RG (X) -2SFL**** (150)	11.0	4.0	0.8	15.0±1.0	13±3	-	-	-	-	-
	RG (X) -2SFL**** (175)				17.5±1.0						
	RG (X) -3SFL**** (200)	15.0	5.5	0.8	20.0±1.5	18±3	-	-	-	-	-
	RG (X) -14ANFL**** (100)	6.3	2.5	0.6	10.0±1.0	10±2	-	-	-	-	-
	RG (X) -14ANFL**** (125)				12.5±1.0						
	RG (X) -12ANFL**** (125)	9.0	2.8	0.7	12.5±1.0	13±3	-	-	-	-	-
	RG (X) -12ANFL**** (150)				15.0±1.0						
	RG (X) -1ANFL**** (150)	11.0	4.0	0.7	15.0±1.0	13±3	-	-	-	-	-
	RG (X) -1ANFL**** (175)				17.5±1.0						
	RG (X) -2ANFL**** (200)	15.0	5.5	0.8	20.0±1.5	18±3	-	-	-	-	-
	RW-12FL**** (125)	9.0	3.5	0.7	12.5±1.0	13±3	-	-	-	-	-
RW-12FL**** (150)				15.0±1.0							
RW-1FL**** (150)	11.0	4.0	0.8	15.0±1.0	13±3	-	-	-	-	-	
RW-1FL**** (175)				17.5±1.0							
RW-2FL**** (200)	15.0	5.5	0.8	20.0±1.5	18±3	-	-	-	-	-	
RQA-14FL**** (100)	6.3	2.3	0.6	10.0±1.0	10±2	-	-	-	-	-	
RQA-14FL**** (125)				12.5±1.0							
RQA-12FL**** (125)	9.0	2.8	0.7	12.5±1.0	13±3	-	-	-	-	-	
RQA-12FL**** (150)				15.0±1.0							
RQA-1FL**** (150)	11.0	4.0	0.8	15.0±1.0	13±3	-	-	-	-	-	
RQA-1FL**** (175)				17.5±1.0							
RQA-2FL**** (200)	15.0	5.5	0.8	20.0±1.5	18±3	-	-	-	-	-	

※標準包装数量：100pcs

※上記以外の加工寸法にも対応できる場合がありますのでお問い合わせ下さい。

# リード線加工(バルク)品



形状 記号・図	型名	寸法 (mm)										
		L	D	d	P	h	h <sub>1</sub>	K	ℓ	ℓ <sub>1</sub>	do	
<b>P, H</b> 	RG(X)-12SP****(100)	6.3	2.5	0.6	10.0±1.5	9.5±3	4.0±1.5	1.2	-	4.0±1.5	0.8	
	RG(X)-1SP****(125)	9.0	2.8	0.7	12.5±1.5	9.5±3	4.0±1.5	1.3	-	4.0±1.5	0.8	
	RG(X)-2SH****(150)	11.0	4.0	0.8	15.0±1.5	13±3	6.0±2.0	1.4	-	5.0±1.5	1.0	
	RG(X)-3SH****(200)	15.0	5.5	0.8	20.0±1.5	18±3	10.0±2.0	1.4	-	5.0±1.5	1.0	
	RG(X)-14ANP****(100)	6.3	2.3	0.6	10.0±1.5	10±2	4.0±1.5	1.2	-	4.0±1.5	0.8	
	RG(X)-12ANP****(125)	9.0	3.5	0.7	12.5±1.5	10±2	4.0±1.5	1.3	-	4.0±1.5	0.8	
	RG(X)-1ANH****(150)	11.0	4.0	0.7	15.0±1.5	13±3	6.0±1.5	1.4	-	5.0±1.5	1.0	
	RG(X)-2ANH****(200)	15.0	5.5	0.8	20.0±1.5	18±3	10.0±1.5	1.4	-	5.0±1.5	1.0	
	RW-12P****(125)	9.0	3.5	0.7	12.5±1.5	10±2	4.0±1.5	1.3	-	4.0±1.5	0.8	
	RW-1H****(150)	11.0	4.0	0.8	15.0±1.5	13±3	6.0±1.5	1.4	-	5.0±1.5	1.0	
	RW-2H****(200)	15.0	5.5	0.8	20.0±1.5	18±3	10.0±1.5	1.4	-	5.0±1.5	1.0	
<b>V</b> 	a	RD-S2V****	3.3	1.7	0.45	-	5.5max	-	-	28±3	15min	-
		RO-S2V*****	3.3	1.7	0.45	-	5.5max	-	-	28±3	15min	-
	b	RD-25V****	6.3	2.3	0.6	-	8.5±1.0	-	2.5max	28±3	12min	-
		RD-S1V****	6.3	2.3	0.6	-	8.5±1.0	-	2.5max	28±3	12min	-
		RD-50V****	8.5	2.8	0.7	-	10±1.0	-	2.5max	28±3	10min	-
		RO-25V*****	6.3	2.3	0.6	-	8.5±1.0	-	2.5max	28±3	12min	-
		RO-S1V*****	6.3	2.3	0.6	-	8.5±1.0	-	2.5max	28±3	12min	-
		RO-50V*****	8.5	2.8	0.7	-	10±1.0	-	2.5max	28±3	10min	-
		RG(X)-12SV****	6.3	2.5	0.6	-	8.5±1.0	-	2.5max	28±3	12min	-
		RG(X)-1SV****	9.0	2.8	0.7	-	11±1.0	-	2.5max	28±3	10min	-
		RG(X)-2SV****	11.0	4.0	0.8	-	14±1.0	-	2.5max	28±3	15min	-
		RG(X)-3SV****	15.0	5.5	0.8	-	17±1.5	-	2.5max	25±3	12min	-
		RG(X)-14ANV****	6.3	2.3	0.6	-	8.5±1.0	-	2.5max	28±3	12min	-
		RG(X)-12ANV****	9.0	2.8	0.7	-	11±1.0	-	2.5max	28±3	10min	-
		RG(X)-1ANV****	11.0	4.0	0.8	-	14±1.0	-	2.5max	28±3	15min	-
		RG(X)-2ANV****	15.0	5.5	0.8	-	17±1.5	-	2.5max	25±3	12min	-
		RQA-14V****	6.3	2.3	0.6	-	8.5±1.0	-	2.5max	28±3	12min	-
		RQA-12V****	9.0	2.8	0.7	-	11±1.0	-	2.5max	28±3	10min	-
		RQA-1V****	11.0	4.0	0.8	-	14±1.0	-	2.5max	28±3	15min	-
		RQA-2V****	15.0	5.5	0.8	-	17±1.5	-	2.5max	25±3	12min	-

※標準包装数量：100pcs

※上記以外の加工寸法にも対応できる場合がありますのでお問い合わせ下さい。また、下記形状についての詳細は、お問い合わせ下さい。

<b>S</b> 	<b>W</b> 
--------------	--------------